

# ZIC SUPER A

## 50 / 55

### High Quality Antifreeze Coolant

INDUSTRIAL OIL

#### GENERAL CHARACTERISTICS \_\_

- Carefully selected inhibitors provide anti-foam, anti-rust and anti-corrosion properties
- ZIC SUPER A provides excellent cooling system protection under the most severe conditions when used as recommended
- ZIC SUPER A is safe to use in systems containing aluminum components

#### DESCRIPTION \_\_

ZIC SUPER A is a high quality antifreeze (ethylene glycol based) long life coolant that provides outstanding performance in most applications. ZIC SUPER A helps to keep vehicle's engine temperature stable in all climates by transferring heat from the engine to the radiator. ZIC SUPER A is conveniently pre-diluted and mixed with a 50:50 ratio of water and antifreeze.

#### SPECIFICATION \_\_

##### SUPER A 50 / SUPER A 55

- Meets ASTM D 3306, KS M2142, BS6580, JIS K2234
- Meets specifications of many major automobile manufacturers

#### RECOMMENDATIONS \_\_

- All vehicle types such as passenger car, heavy truck and bus
- High-speed and heavy-duty vehicles that require a high boiling point and load-bearing performance
- Vehicles for adverse driving such as high-speed racing and mountainous terrain

#### TYPICAL PROPERTIES \_\_

Product Name	SUPER A 50	SUPER A 55
Color	GREEN	GREEN
Freezing Point, °c	-35	-45
pH	8.20	8.22
Specific Gravity, 15°C	1.078	1.081
Water content	50%	45%
Metal corrosion test	Pass	Pass

