

ZIC ATF MULTI

Fully Synthetic Automatic Transmission Fluid - ATF for Multi Vehicle (Multi-Purpose)

FULLY SYNTHETIC | DRIVELINE FLUIDS

GENERAL CHARACTERISTICS __

- Effective wear protection and improved oxidation and corrosion resistance to protect transmission components
- Compatible with a wide range of automatic transmission from multiple manufacturers
- Exceptional friction control performance providing smooth gear changes

DESCRIPTION __

ZIC ATF Multi is a fully synthetic automatic transmission fluid suitable for a wide range of passenger cars. It offers excellent friction characteristics and superior performance in smooth shifting and noise reduction through thick film retention in high temperature.

SPECIFICATION __

ATF MULTI

- HYUNDAI/KIA SP-II/III/IV/IV-RR, Red-1/1K, M-1375.4, NWS-9638; GM ATF II/III/VI; FORD Mercon, Mercon V/LV; MB 236.1/2/3/5/6/7/9/10/11/12/14/15/41/81; BMW 7045E, 8072B, LA2634, LT71141, 83 22 0 142 516, 83 22 2 152 426 VW/AUDI G 052 162/540/990, G 055 005/025/162, G 060 162; VOLVO 97325/97335, CE 97340, PN 1161521/540/621/640; RENAULT DP-0; PSA AL-4; SAAB 93 165 147; PORSCHE T-IV (JWS 3309); TOYOTA/LEXUS T, T-II/III/IV/WS (JWS 3324); HONDA/ACURA ATF Z-1, DW-1; NISSAN/INFINITI Matic-D/J/K/S/W; ALLISON C-3/4, TES-295/389/389B; AISIN AW-1; JASO 1-A, 1-A-LV

RECOMMENDATIONS __

- Recommended for automatic transmissions listed on specification and on the label

TYPICAL PROPERTIES __

Product Name	ATF MULTI
Color	RED
Density, g/cm ³	0.845
Kinematic Viscosity at 40°C, cSt	35.8
Kinematic Viscosity at 100°C, cSt	7.01
Viscosity Index	161
TAN, mgKOH/g	1.4
Flash Point, °C	220
Pour Point, °C	-48
Brookfield Viscosity, cP, -40°C	14,700

